



OAK COSENZA

Oak Cosenza is a very rustic, natural product. Dark filled cracks and knots as well as color variations from light to dark are common features.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES			
Article Number	151N9LEK09KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%	
Surface Treatment	Matt lacquer	Design	1-strip	Minimum Mean Density kg/m ³		>500 kg/m ³	
Refining Treatment	Microbevelled 4-sided	Grading	Country	Reaction To Fire	EN13501-1	Dfl-s1	
Dimensions	2420 x 187 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1	
Weight per Package	22 kg	Resandable	2-3 times	Content PCP	CEN/TR14823	≤ 5 x 10-6n	
Area per Package	2.72 m ²	Natural/Stained	Natural	Breaking Strength N/mm ²	EN1533	NPD	
Area Per Board	0.453 m ²	Brinell Value	3, 7	Thermal Conductivity	EN12664	0,14 W/mK	
DETAIL DESCRIPTION		Joint	Woodloc® 5S	Thermal Resistance R-Value		.59 (m2KW)	
All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		Floor heating	Yes	Biological Durability	EN350-2	Class 1	
		Warranty	30 years	CARB2		Compliant	
		Wear-layer material	Hardwood				
		Wear-layer thickness	3,0 mm				
		Core material	Pine/Spruce lamella				
COLOUR CHANGE		Thickness	15 mm				
Some muting of colour variation to medium, straw brown.		Installation method	Floating, glue-down				
		EAN Code	7393969038348				

CERTIFICATES

