



Kährs
QUALITY IN WOOD SINCE 1857

OAK ESTORIL

Oak Estoril is a classic floor, where the natural wood characteristics has been enhanced with microbevel and brushing topped with a white stained natural oil.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151N8AEKFKW220	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Oil	Design	1-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Refining Treatment	Microbevelled 4-sided, brushed	Grading	Country	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2266 x 187 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	21 kg	Collection	Sand Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2, 54 m ²	Natural/Stained	Stained	Breaking Strength N/mm ²	EN1533	NPD
Area Per Board	0, 423 m ²	Brinell Value	3, 7	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Joint	Woodloc® 5S	Thermal Resistance R-Value		.59 (m2KW)
Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.		Floor heating	Yes	Biological Durability	EN350-2	Class 1
COLOUR CHANGE		Wear-layer material	Hardwood	CARB2		Compliant
Stained product - noticeable color change over time.		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969041249			
		Surface Colour	White			

CERTIFICATE

