



OAK COMO

Oak Como is a floor with strips selected to provide a calm appearance but still with certain degree of variation in the grain.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153N38EK50GW0	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Silk lacquer	Board	3-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Dimensions	2423 x 200 x 15 mm	Grading	Variation (Town)	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	23 kg	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Area per Package	2.91 m ²	Collection	European Naturals Collection	Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Area Per Board	0.485 m ²	Resandable	2-3 times	Breaking Strength N/mm ²	EN1533	NPD
DETAIL DESCRIPTION		Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK
Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers.		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2KW)
COLOUR CHANGE		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Some muting of colour variation to medium, straw brown.		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969030236			

CERTIFICATES

